

M I R A B E L L A

Content	100% Nylon Fiber Matrix
Width	55 inch/140 cm
Weight	170 - 230 g/m ²
Thickness	24 mils; 0.6 mm
Cleanability Code	S/W
Wear	100,000+ double rubs Wyzenbeek Wire screen (ASTM D-4157-82) *
Crock	Wet 5/Dry 5 (AATCC-8-1988)
Trap Tear Strength	30 lbs x 30 lbs (ASTM D-1117-80)
Grab Tensile Strength	100 lbs x 100 lbs (ASTM D-5034-90)
Seam Strength	100 lbs x 100 lbs (ASTM D-1683-90A)
Colorfastness: Gas Fumes	(AATCC-23, 3 cycles) Class 4-5/Little to no color change
Colorfastness: I	• Light Stability (AATCC-16A-82) Class 4-5/40 hrs. min. • Water (AATCC 107-1981) Class 4-5 • Perspiration (AATCC 15- 1979) Class 4-5 • Dry Cleaning (AATCC 132-1979) Class 4-5
Colorfastness: II	Sulfide Staining (ASTM D-1712-89) No staining
Flammability Class I	UFAC/NFPA 260-1989
Flammability Pass	California Technical Bulletin 117-2013 Section 1 - Pass
Flammability Class A Rated	Tunnel Test (ASTM E84)**
Flame Compatibility	Can also be treated to meet many international flammability codes.

**Tested as MIRABELLA with backing by both adhered and unadhered method.

MAJILITE